



1632 GRADER/BOX SCRAPER

Because dirt is never
in the right place

- ✓ 16' x 32" blade, with standard 6" cutting edges.
- ✓ Three way operation to raise/lower, tilt side to side, and rotate blade.

- ✓ Pintle hitch design.
- ✓ 300 engine horsepower maximum tractor power.
- ✓ Blade swing left to right is 50°, tilt side to side is 15°, blade clearance at full raised position is 30".
- ✓ Overall length is 21'. Overall width with hydraulic blade swing is 9' 6". And transport width is 8' 4" with the blade cylinders unpinned and placed in transport position.
- ✓ 19 x 16.1 tires, with 8 bolt rims, and 8000 lb. spindles.
- ✓ Weight box on rear to be filled before use.
- ✓ Hydraulic cushion valve for blade breakaway.
- ✓ Lighting package is standard.
- ✓ Hydraulic cylinders are welded industrial—5 x 24 blade swing, 4 x 12 tilt, 4 x 16 raise/lower.
- ✓ Standard fold-down box ends to switch from grader to box scraper in minutes.

ICON Industries, Inc.

A LANDOLL® Company

1600 W. 8th Street • Beloit, Kansas 67420

(785)738-6613 • www.iconindinc.com

ICON reserves the right to change models, designs, and/or specifications without notice or obligation.

