



# 2215/2217

## LANDOLL 2215/2217 WEATHERPROOFER I



**Model 2215-6-30 With Straight Leg Shanks**



**Model 2217-7-30 with Parabolic Shanks**

**3** YEAR  
WARRANTY

### **CUT AND SIZE RESIDUE AND DEEP-TILL COMPACTION ZONES ALL IN ONE PASS.**

Landoll's double offset tandem disc gangs assure you 100% disc cut in front of the shanks. Landoll offers 22" diameter by 1/4" disc blades with Rock-Flex protection. Optional 24" diameter by 1/4" disc blades are available. Coil spring automatic reset clamps with parabolic (37" x 1-1/8" x 3") or heavy duty straight leg (37" x 1-1/4" x 4") shanks with slide on roll pin points. Shanks work up to 18" deep. If an obstacle is encountered, the shank will trip up to 14" and reset automatically. Unique disc cut angle settings allow for adjusting of all four gangs. Choose from 10, 15 or 20 degree cutting angle to leave the amount of residue preferred for conservation compliance. Landoll offers you a choice of 24" or 30" shank spacing. Sizes available from 3 shank to 9 shank.



## STANDARD SPECIFICATIONS

### FRAME

- 6" x 3" Heavy Wall Tubing on 2215
- 6" x 4" Heavy Wall Tubing on 2217

### DISC GANGS

- Double Offset Tandem Disc Gangs
- Regreaseable Disc Bearings
- 20" Feathering Blades
- 22" Disc Blades
- 15" Disc Spacing
- Up to 6" Cutting Depth
- Three Disc Cutting Angles  
- 10°, 15° and 20°

### HITCH

- Long T-Type Hitch
- Level Lift Linkage
- Radius Rod to Level Machine
- Cat. III or IV Pintle Type Clevis

### SHANKS

- Two Shank Options, Parabolic or Straight Leg Shanks
- Coil Spring Auto-Reset Shank Protection

### AXLE/RIMS

- Single Axles on 2215
- Walking Tandems on 2217
- Hydraulic Lift with 4x10 Cylinders

### OTHER

- Hydraulic Hoses with Couplers to Tractor
- Warning Lights
- Wrenches for Gang Bolt and Angle Adjustment
- Storage Trays

## MODEL SPECIFICATIONS

Model Number	Number of Discs	Number of Shanks	Shank Spacing	Transport Width	Working Width	Walking Tandems
2215-3-30	16	3	30"	9'-0"	9'-0"	no
2215-4-24	16	4	24"	9'-0"	9'-0"	no
2215-4-30	20	4	30"	11'-4"	11'-4"	no
2215-5-24	20	5	24"	11'-4"	11'-4"	no
2215-5-30	24	5	30"	14'-2"	14'-2"	no
2215-6-30 *	24	5	30"	14'-2"	14'-2"	yes
2215-6-30	28	6	30"	16'-0"	16'-0"	No
*Denotes Dual Wheels						
2217-5-30	24	5	30"	14'-2"	14'-2"	yes
2217-6-30	28	6	30"	16'-0"	16'-0"	yes
2217-7-24	24	7	24"	14'-2"	14'-2"	yes
2217-7-30	32	7	30"	18'-4"	18'-4"	yes
2217-8-30	36	8	30"	20'-9"	20'-9"	yes
2217-9-24	32	9	24"	18'-4"	18'-4"	yes



Continuous product improvement is a Landoll goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment, and prices with out prior notice and without changes on previous models.

