



# 2320

**LANDOLL SERIES 2320 WEATHERPROOFER II**



**3** YEAR  
WARRANTY



# Landoll Series 2320 We



## DISC BLADES AND SCRAPERS

Landoll features adjustable scrapers as standard equipment on both front and rear gangs. They are attached directly to the bearing mounts by spring steel so they move together.



## DISC GANG BEARINGS

The heavy duty, self-aligning, rubber cushioned disc gang bearings are greaseable, and combined with heavy cast half spools, will give long reliable service in the toughest conditions.



## UNIQUE DISC GANG ANGLE SETTINGS

Unique disc gang angle settings allow for adjusting all four gangs in minutes. Choose from 10°, 15°, or 20° cutting angle to leave the amount of residue preferred.



## EXCLUSIVE AUTO-RESET CLAMPS WITH 37" PARABOLIC SHANKS

Exclusive automatic reset clamps and 37" parabolic shanks with wearshin and drive on points, allow for trouble-free operation. Shanks work up to 18" deep. If an obstacle is encountered, the shank will trip up to 14" and reset automatically. You have a choice of either 24" or 30" shank spacing.

# Weatherproofer II - Leading the Way



**FLAT POINT**



**7" WING POINT**



**SHARK FIN POINT**



**V-CAP POINT**



## **NARROW TRANSPORT**

The 7 to 10 shank models of the 2320F fold to a safe narrow transport width of 12.9' to 16.1'.



# WEATHERPROOFER II SPECIFICATIONS

## STANDARD SPECIFICATIONS

### FRAME:

- 6" x 3" x 3/8" Tubing on 2325 Models
- 6" x 4" x 3/8" Tubing on 2327 Models
- 8" x 4" x 3/8" Tubing on 2320F Models

### DISC GANGS:

- Hydraulic Depth Control
- Regreaseable Disc Bearings
- 20" x 1/4" Feathering Blades
- 22" x 1/4" Disc Blades
- 13" Disc Spacing on Front Gangs
- 10" Disc Spacing on Rear Gangs
- Three Disc Spacing on Rear Gangs
- Three Disc Cutting Angles - 10°, 15° and 20°
- Rock Flex Mounted Disc Gangs

### SHANKS:

- Auto-Reset Shank with 3,900 lb. Points.
- Parabolic Shanks - 37" x 1-1/8" x 3"
- 37" Underframe Clearance
- 2" Steel Flat Point with Wear Guard

### HITCH:

- Hydraulic Swing Hitch on 2320F
- Level Lift Linkage
- Cat. III or IV Pintle Type Clevis

### OTHER:

- Warning Lights
- Safety Chain
- Powder Coat Paint

### AXLE/RIMS:

- Single axles with 6-Bolt Hubs and 11Lx15 Tires
- On Model 2325-3-30, 2325-4-24, 2325-4-30 and 2325-5-24
- Single Axles with 8-Bolt Hubs and 11Lx15 Tires on Model 2325-5-30 and 2325-6-30 and 2325-5-24
- Single Axles with 8-Bolt Hubs and 11Lx15 Tires on Model 2325-5-30 and 2325-6-30
- Walking Tandems with 8-Bolt Hubs and 11Lx15 Tires on 2327 and 12.5L x 15 Tires on 2320F Models

## OPTIONAL SPECIFICATIONS

### AXLES/RIMS:

- Six Bolt Dual Wheels for 2325-5-30 Only
- Eight Bolt Hubs and Wheels available for Model 2325-3-30, 2325-4-24, 2325-4-30 and 2325-5-30

### POINTS:

- 2-3/8" V-Point (Chrome)
- 2-3/8" Shark Fin Point (Chrome)
- 7" Wing Point (Chrome)

### DISC BLADES:

- 24" x 1/4" Disc Blade

## MODEL SPECIFICATIONS

Model Number	Number of Discs	Number of Shanks	Shank Spacing	Transport Width	Working Width	Walking Tandems	Approximate Weight (lbs)
2325-3-30	20	3	30"	10'-11"	10'-1"	no	6860
2325-4-24	20	4	24"	10'-11"	10'-1"	no	7060
2325-4-30	28	4	30"	12'-5"	11'-7"	no	7120
2325-5-24	28	5	24"	12'-5"	11'-7"	no	7590
2325-5-30	32	5	30"	15'-7"	14'-9"	no	8210
2325-6-30	36	6	30"	17'-3"	16'-5"	no	8690
2327-5-30	32	5	30"	15'-7"	14'-9"	yes	10290
2327-6-30	36	6	30"	17'-3"	16'-5"	yes	10550
2327-7-24	36	7	24"	17'-7"	16'-9"	yes	10760
2327-7-30	42	7	30"	20'-9"	19'-11"	yes	11280
2327-8-30	46	8	30"	22'-5"	21'-7"	yes	11900
2327-9-24	42	9	24"	20'-9"	19'-11"	yes	11690
2320F-7-30	42	7	30"	13'-8"	19'-1"	yes	15708
2320F-8-24	38	8	24"	12'-11"	17'-5"	yes	15647
2320F-8-30	46	8	30"	14'-6"	20'-8"	yes	16514
2320F-9-30	52	9	30"	16'-1"	23'-10"	yes	17329
2320F-10-24	46	10	24"	14'-6"	20'-8"	yes	16964

Landoll continuously improves product, therefore, we reserve the right to make any changes in illustrations, specifications, equipment, and prices with out prior notice and without changes on previous models.



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • [www.landoll.com](http://www.landoll.com)

