



# ***3110/3130 PACKER***



**Breaks Clods while it Gently Firms and Levels Seedbeds  
Reducing Air Pockets and Moisture Loss  
Stimulate Seed Germination for Uniform Plant Stands**

**3** YEAR  
WARRANTY

## 3110/3130 PACKER- THE VERSATILE PACKER LINE

Transport wheels, standard on the 3110/3130 Packers, clear the ground so there are no machine tire tracks to spoil your ideal seedbed which has just been prepared. Dual wheels are standard on the Packer for machines 27'-7" and wider and optional on the 19'-1" to 24'-9" machines.

Hydraulics provide for cab control convenience in transporting your Landoll Packer.

Landoll 3110/3130 Packers are available in sizes from 10'-0" through 36'-0" to fit every application. A rugged super-structure and a flat fold mechanism allow a transport width of only 13'-6". The cross-over design allows the wings of the larger units to bypass each other in the folded position. Unlimited upward float and 5 degrees downward float is also provided for. A single hydraulic control operates all functions on the 3110/3130 Packer. A simple movement of the hydraulic lever places the Packer in transport position, then the wings into their flat storage position. Reversing the sequence, the center section is first lowered to the ground, followed by the wings unfolding. Wide based hitch, which distributes load, is standard on all folding models. Ductile Iron Wheels: Landoll packers use 19" heavy-duty 6-spoke smooth rollers to evenly spread shock loads throughout the entire roller. 20" Crowfoot rollers provide more aggressive clod breaking and the soil is left with a loosely mulched surface. Reversing crowfoot rollers leaves small pockets in the soil, which will increase moisture retention and provide better wind and water control.



- The 27'-7" to 36'-0" Wing Packers are equipped with a telescoping tongue, which increases maneuverability for making sharp turns in the field, yet reduces its length for road travel and more convenient storage.



- 1-3/4" Solid Gang Shaft
- Triple Sealed Greasable Bearing



## MODEL SPECIFICATIONS

Model Number	S/R Rolling Width	CF Rolling Width	Transport Width	No. Of Roller/Gang		S/R Approx. Weight	CF Approx. Weight
				Smooth 19"	Crowfoot 20"		
3110-10	9'-11"	9'-9"	10'-7"	28	18	1,406 lbs.	1,198 lbs.
3110-12	12'-0"	11'-11"	12'-7"	34	22	1,660 lbs.	1,414 lbs.
3110-14	14'-3"	14'-10"	14'-10"	40	27	1,940 lbs.	1,678 lbs.
3110-16	16'-11"	16'-1"	16'-11"	46	31	2,240 lbs.	1,936 lbs.
3130-19	19'-1"	19'-1"	13'-6"	55	37	3,962 lbs.	3,601 lbs.
3130-20	20'-7"	20'-7"	13'-6"	59	41	4,145 lbs.	3,913 lbs.
3130-22	22'-8"	22'-8"	13'-6"	65	45	4,402 lbs.	4,031 lbs.
3130-24	24'-9"	24'-9"	13'-6"	71	47	4,664 lbs.	4,178 lbs.
3130-27	27'-7"	27'-7"	13'-6"	79	53	6,184 lbs.	5,665 lbs.
3130-31	31'-9"	31'-9"	13'-6"	91	61	6,748 lbs.	6,161 lbs.
3130-36	36'-0"	36'-0"	13'-6"	103	69	7,322 lbs.	6,675 lbs.



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • [www.landoll.com](http://www.landoll.com)

Landoll continuously improves product, therefore, we reserve the right to make any changes in illustrations, specifications, equipment, and prices without prior notice and without changes on previous models.

