




3210/3230 MULCHER




***Mulch, Firm and Level Seedbeds
to Reduce Air Pockets,
Conserve Moisture and Produce More
Uniform Seed Germination***


3 YEAR
WARRANTY



Ductile Iron Wheels: Landoll packers use 19" heavy-duty 6-spoke smooth rollers to evenly spread shock loads throughout the entire roller.



Crowfoot Rollers provide aggressive clod breaking action, leaving the soil with a loosely mulched surface. Reversing crowfoot rollers increases moisture retention, help control erosion and prevent crusting.



Two Tine Options: Unlike "C" Tines on competitive machines which are susceptible to plugging because residue can travel up the tooth and lodge on the tooth bar. Rugged Looped "C" tines vibrate and pull moisture to the surface, drop residue on the ground so the residue passes under the rollers. Extra Heavy-Duty Danish "S" tine has more vibrating action to rapidly stir the soil to eliminate stubborn clods and air pockets.

Hydraulic Depth Control - A single hydraulic cylinder controls transport height and tooth depth on 10' to 25' machines. The 30' machine features an individually operated hydraulic tooth depth control (optional on all other machines).



Scrapers on the rear and smooth rollers of all mulchers are individually adjustable and reversible. Front scrapers are also available for unusually wet sticky soil.



Land Leveler Bar (optional) attaches in front of the front rollers to break and level large clods prior to mulching. Height is adjustable to accommodate varying soil conditions.



Weight Transfer is needed on some fields for best mulching results. Unique Weight Transfer System allows weight to be distributed between the front and rear rollers and the draw bar as needed.

MODEL SPECIFICATIONS

Model Number	Rolling Width	Transport Width	No. Of Rollers/Gang Transport Width		Number of Tines	Est. Weight
			Smooth 17" & 19"	Crowfoot 17" & 20"		
3210-10	10'-7"	10'-7"	28	19	19	3,577 lbs. - 4,817 lbs.
3210-12	12'-10"	12'-10"	34	34	23	4,542 lbs. - 5,351 lbs.
3210-13	13'-10"	13'-10"	36	36	25	4,796 lbs. - 5,592 lbs.
3210-14	14'-10"	14'-10"	39	39	27	4,914 lbs. - 6,031 lbs.
3210-15	15'-11"	15'-11"	42	42	29	5,218 lbs. - 6,264 lbs.
3210-18	18'-7"	18'-7"	50	50	35	6,958 lbs. - 7,890 lbs.
3230-21	21'-11"	14'-2"	60	60	39	8,841 lbs. - 10,294 lbs.
3230-25	25'-5"	14'-2"	72	72	46	9,815 lbs. - 11,522 lbs.
3230-30	30'-2"	16'-4"	82	82	57	10,381 lbs - 11,941 lbs



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • www.landoll.com

