



LANDOLL 1550 IN-RROW RIPPER



3 YEAR
WARRANTY

Manage your soil or your soil will manage you.

The Model 1550 is the ideal tool for the control of compaction and residue. A choice of two shanks and four different points lets you choose the ground engaging tool that best fits your tillage practice. A 20" coulters in front of the shank slices the residue to eliminate plugging. This revolutionary new tool allows you control of compaction, increase of water intake in wet weather, and reverse capillary action in times of dry weather. The model 1550 is the ideal Soil Manager.



FEATURES AND OPTIONS



Parabolic Shank



HD Straight Leg



Flat Point



7" Wing Point



Shark Fin Point



V-Cap Point



Screw Adjustable Gauge Wheels



Adjustable Spring-Loaded Coulters



Adjustable Coverboards

MODEL SPECIFICATIONS

Five Frames to Choose From

- "A" Mainframe - Rigid 8' (2.44M) and
- "B" Mainframe - Rigid 11' (3.35M)
- Double Bar 4" x 6" (101.6mm x 152.4mm) Tubing
- Bolt on Wing Extensions (17" or 27" (431.8mm or 685.8mm))
- 3, 4, 5, 6 and 7 Shanks
- Welded 3-point Hitch with Cat II and Cat III Pins
- "C" Mainframe - Rigid 13' (3.96M)
- Double Bar 4" x 6" (101.6mm x 152.4mm) Tubing
- Bolt on Wing Extensions (17" or 27" (431.8mm or 685.8mm))
- 6, 7, and 8 Shanks
- Welded 3-point Hitch with Cat III Pins

"D" and "E" Mainframes Folding

- Double Bar 4" x 6" (101.6mm x 152.4mm) Tubing
- Hydraulic Wings 33" (838.2mm), 46" (1168.4mm), and 60" (1524mm)
- 6, 7, 8, and 9 Shanks
- Hydraulic Fold Wings
- Welded 3-point Hitch with Cat III Pin

Shank Spacing

- 30" (762mm), 36" (914.4mm), 38" (965.2mm) and 40" (1016mm)

Horsepower Requirements

- 25 to 45 PTO Horsepower per Shank

Coulters

- 20" (508mm) Diameter
- Adjusting Spring Cushion

Gauge Wheels - Standard

- 2 per Machine
- 20.5 x 8 Tires
- Screw Adjustable

Optional Equipment

- Bedding Attachment (Available in 4, 6, and 8 Row Models)
- Coverboard



Continuous product improvement is a Landoll goal. Therefore, we reserve the right to make any changes in illustrations, specifications, equipment, and prices without prior notice and without changes on previous models.

1900 North Street • Marysville, KS 66508 • (785) 738-6613 • www.landoll.com

