



8500 Series Finisholl Specifications

Double Spike and Double Chevron Reel

Adapts To:	8530-19	8530-22
Approximate Weight	3,591 lbs. (1,629 kg)	4,158 lbs. (1,886 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 4 in. (102 mm) Spacing	Overall 4 in. (102 mm) Spacing
Spike Angle Adjustment	Variable Tooth Pitch Adjustment	Variable Tooth Pitch Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	(2) Round Bar Chevron Reels	(2) Round Bar Chevron Reels
Section Sizes	6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m)	7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m)

Adapts To:	8530-25	8530-27
Approximate Weight	4,725 lbs. (2,143 kg)	5,103 lbs. (2,315 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 4 in. (102 mm) Spacing	Overall 4 in. (102 mm) Spacing
Spike Angle Adjustment	Variable Tooth Pitch Adjustment	Variable Tooth Pitch Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	(2) Round Bar Chevron Reels	(2) Round Bar Chevron Reels
Section Sizes	7.75 ft. (2.4 m) -- 4.5 ft. (1.4 m) -- 5 ft. (1.5 m) -- 7.75 ft. (2.4 m)	7.5 ft. (2.3 m) -- 6.25 ft. (1.9 m) -- 6.25 ft. (1.9 m) -- 7.5 ft. (2.3 m)

Adapts To:	8530-30	8530-33
Approximate Weight	6,522 lbs. (2,958 kg)	5,820 lbs. (2,640 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 4 in. (102 mm) Spacing	Overall 4 in. (102 mm) Spacing
Spike Angle Adjustment	Variable Tooth Pitch Adjustment	Variable Tooth Pitch Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	(2) Round Bar Chevron Reels	(2) Round Bar Chevron Reels
Section Sizes	9 ft. (2.7 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 9 ft. (2.7 m)	9 ft. (2.7 m) -- 7.75 ft. (2.4 m) -- 7.75 ft. (2.4 m) -- 9 ft. (2.7 m)

Adapts To:	8530-35	8550-38
Approximate Weight	6,215 lbs. (2,819 kg)	7,182 lbs. (3,258 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 4 in. (102 mm) Spacing	Overall 4 in. (102 mm) Spacing
Spike Angle Adjustment	Variable Tooth Pitch Adjustment	Variable Tooth Pitch Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	(2) Round Bar Chevron Reels	(2) Round Bar Chevron Reels
Section Sizes	10 ft. (3.0 m) -- 7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m) -- 10 ft. (3.0 m)	6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m)

Adapts To:	8550-43	8550-48
Approximate Weight	7,483 lbs. (3,394 kg)	7,799 lbs. (3,538 kg)
Teeth	0.75 in. x 14 in. (19.1 x 356 mm)	0.75 in. x 14 in. (19.1 x 356 mm)
Teeth Spacing	Overall 4 in. (102 mm) Spacing	Overall 4 in. (102 mm) Spacing
Spike Angle Adjustment	Variable Tooth Pitch Adjustment	Variable Tooth Pitch Adjustment
Reel Diameter	12 in. (305 mm)	12 in. (305 mm)
Reel Bars	(2) Round Bar Chevron Reels	(2) Round Bar Chevron Reels
Section Sizes	7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 7.5 ft. (2.3 m) -- 7.5 ft. (2.3 m)	8.5 ft. (2.6 m) -- 9 ft. (2.7 m) -- 6.5 ft. (2.0 m) -- 6.5 ft. (2.0 m) -- 9 ft. (2.7 m) -- 8.5 ft. (2.6 m)