



2000 ROW CROP CULTIVATOR



ROW CROP CULTIVATOR SPECIFICATIONS

STANDARD EQUIPMENT

- 7" x 7" Heavy Wall Toolbar
- Wide Parallel Linkage with Heavy Duty Down Pressure Springs
- 6 x 4 Gang Frames
- 20" Adjustable Coulters
- 16" Penetrator Sweeps on 30" Rows
- 24" Penetrator Sweeps on 36", 38" and 40" Rows
- Fork-Mounted Gauge Wheels with 4.6" x 16" Hard Rubber Tires
- Category II 3 pt. Hitch for 4-8 Row Units
- Category III 3 pt. Hitch for 10-16 Row Units

AVAILABLE OPTIONS

- Shields
- 4" Ridgers
- 8" Ridgers (Irrigations)
- Anhydrous Knife Assemblies
- 14" Disc Hillers
- Liquid Fertilizer Spray Attachments
- Lift Assist Wheels
- Row Crop Tank Hitch



MODEL SPECIFICATIONS

Model Number	Number of Rows	Row Spacing	Approximate Weight	Transport Height	Transport Width
RIGID FRAME MODELS					
2004-30HC	4	30"	2,100 lbs.	-	11'0"
2004-36HC	4	36" / 38"	2,225 lbs.	-	13'6"
2006-30HC	6	30"	3,000 lbs.	-	16'0"
2006-36HC	6	36" / 38"	3,131 lbs.	-	20'0"
2008-30HC	8	30"	3,872 lbs.	-	21'0"
2008-36HC	8	36" / 38"	4,046 lbs.	-	26'3"
2008-40HC	8	40"	4,070 lbs.	-	27'8"
2010-30HC	10	30"	5,500 lbs.	-	26'3"
FLAT FOLDING MODELS					
2006-36HCF	6	36" / 38"	3,989 lbs.	9'10"	11'6"
2008-30HCF	8	30"	4,730 lbs.	9'10"	12'0"
2008-36HCF	8	36" / 38"	4,905 lbs.	9'10"	15'0"
2008-40HCF	8	38" / 40"	5,035 lbs.	9'10"	16'5"
2010-30HCF	10	30"	5,900 lbs.	9'10"	17'2"
2012-30HCF	12	30"	6,700 lbs.	9'10"	17'2"
2012-36HCF	12	36"	8,151 lbs.	11'10"	21'3"
2012-38HCF	12	38"	8,171 lbs.	11'10"	23'0"
2012-40HCF	12	40"	8,191 lbs.	11'10"	22'6"
2016-30HCF	16	30"	8,663 lbs.	11'10"	22'6"



1900 North Street • Marysville, KS 66508 • (785) 738-6613 • www.landoll.com

Landoll continuously improves products. We reserve the right to make any changes in illustrations, specifications, equipment, and prices without prior notice and without changes on previous models.

